

WIREL_oCK

Dovetail Triangular Tie



WIREL_oCK Dovetail Tri-Ties are a flexible tie used to anchor masonry to concrete. The dovetail fits into a slot attached inside the concrete backup. The hole in the middle of the dovetail also allows the tie to be screwed into the concrete backup if a slot is not being used.

PRODUCT DATA

Wire (cold drawn steel wire)
Conforms to ASTM A82-07
Tensile Strength : 80,000 psi
Yield Point : 70,000 psi minimum

Sheet Metal (Carbon Steel)
ASTM A1008 / A1008M

Hot Dip Galvanized after fabrication / Zinc Coating:
ASTM A153 / A153M-B2 (1.5 oz per sq. ft.)

Stainless Steel (Wire)
ASTM A580 / ASTM A580M

Stainless Steel (Sheet Metal)
ASTM 580 Type 304

FINISHES & SIZES

Finishes:

- Hot Dipped Galvanized after fabrication: ASTM A 153 (1.5 oz per sq. ft.)
- Stainless Steel: ASTM A580—AISI Type 304

Dovetail Gauge:

- 12 Gauge with a 5/16" hole

Available Sizes:

3"x3"	4"x4"
5"x5"	6"x6"
7"x7"	7"x9"

Distributed by:

**JV BUILDING
PRODUCTS**

Masonry Specialty Products Since 1977